

Specifications

Feature Comparison of DTX Models

Feature	DTX-1800	DTX-1200	DTX-LT	DTX-ELT	DTX-CLT	DTX-CLT CertiFiber
Maximum Category/Class	7/F	6/E	6/E	6/E	5e/D	NA
Maximum Frequency (normal, extended)	600 MHz, 800 MHz (RL, NEXT) 900 MHz (IL, NEXT)	250 MHz, 350 MHz	250 MHz, 350 MHz	250 MHz, 350 MHz	100 MHz, 155 MHz	NA
Class F Autotest Time	Less than 25 s	NA	NA	NA	NA	NA
Cat 6 Autotest Time (Cat 5e for the DTX-CLT)	Less than 10 s	Less than 10 s	Less than 25 s	Less than 25 s	Less than 25 s	NA
Supports Fiber Modules	•	•	•		•	•
Supports OTDR Module	•	•	•			
Supports DTX-NSM Module	•	•	•		•	
Supports Coaxial Adapters	•	•	•	•		
Includes AC Wire Map Test	•	•	•		•	
Supports Custom Limits	•	•	•		•	•
Includes Autosave Function	•	•	•		•	•
Includes Patch Cord Test Limits (for use with DTX-PCU6S)	•	•	•		•	
Supports Memory Cards	•	•				
Supports Alien Crosstalk Module	•					